



# Creo Intelligent Fastener 8.0.3.0


*What's New*



# Fixed Bugs

---

- Fixed error "No hole charts found for this hole types" when placing dowel pin Fastener. SPR-8702705
- Fixed problems while regenerating relations.
- A gap was created between the fastener and the placement surface while placing a fastener on very thin models. SPR-13085083
- Reading of \*.hol files in IFX reworked.
- Add corruption check for IFX fastener groups. SPR-10503770
- Option 'GEN\_DIGITS' removed. SPR-12778104
- Rework functionality if 'HOLE\_VISIBILITY' is set to 'NO'. SPR-13074974
- For more information see [changelog.html](#).



# Creo Intelligent Fastener 8.0.2.0

*What's New*




# Enhancements and Fixes

## Enhancements

- Add Additional Tools information offered by B&W Software GmbH

## Bug Fixes

- UI-Strings are not translated in version 8.0.1.0



# Creo Intelligent Fastener 8.0.1.0

*What's New*




# Enhancements and Fixes

## Enhancements

- SPR 11357093: Support unicode characters in param\_relation.txt.
- SPR 11285257: Disallow thread-surfaces as a position reference.
- Add new INCREMENT\_\* options to control the increment value of the spin box for diameter and depth values.
- Support body colors for 2D-preview.

## Bug Fixes

- SPR 12035414: Fix problem while adding a fastener with option assemble fastener on all instances (from a pattern).
- Fix problems in hole chart layout.
- Fix problem with offset '-0.1' for screw-in connections.
- Fix problem with new designated parameters from 'ifx\_start\_mdl.cfg'. If the parameter is also used in a 'param\_relation.txt' then the designation status gets lost.
- Fix for COLOR\_HOLES option.



# Creo Intelligent Fastener 8.0.0.0

*What's New*





# Select hole chart for IFX holes

## Advantages

- Use different hole charts for different fastener types.
- Show different hole notes.
- Control the counterbore diameter with CBOREDIAM.

## Details/ Usage

- Select hole chart for IFX holes if more then one is found.
- Use the new keyword THREAD\_NAME in your fastener data file to preselect a hole chart.






# Add option to control clearance hole behavior

## Advantages

- Use the same behavior than Creo Parametric.
- Allow to disable limits for the hole diameter.

## Details/ Usage

- Control hole diameter behavior in the Screw Fastener Definition dialog box inside the Hole layout.
- Control the limits for the hole and set the diameter to read only.



### *CLEARANCE\_HOLE\_USE\_LIMITS*

- YES – Set limits for min. and max. clearance hole diameter.
- NO – Do not set any limits for clearance hole diameter.

### *CLEARANCE\_HOLE\_DIAMETER\_OVERRIDE*

- CREO\_DEFAULT – Use the value of the *hole\_diameter\_override* configuration option.
- YES – Allow specifying the clearance hole value, instead of the standard value.
- NO – Use the standard clearance hole diameter value.

# Use option *drilled\_hole\_tip\_angle* in IFX

## Advantages

- Intelligent fastener use same settings as Creo Parametric.
- No need to change the tip angle afterwards.

## Details/ Usage

- If the Creo Parametric option *drilled\_hole\_tip\_angle* is set, IFX uses this value.
- If the option is not set, the default angle 118° is used.

